

BCS3SDMG

3-Way, Thin In-Ceiling Speaker

The easy to install BCS3SDMG is 3-way speaker comprising of three 3" woofers , one 3" midrange and one 20mm silk dome tweeter. This speaker is primarily used in MDU construction where poured concrete ceilings/floors are encountered. Typical construction like this needs a speaker with a maximum mounting depth of 2".

The three way design provides a rich bass response with a balanced midrange and high frequency response. The speaker has a removable rear enclosure. When the rear enclosure is in place this prevents sound from migrating into other areas. The front baffle is ported to enhance bass response. In some situations it may be advantageous to remove the rear enclosure for different sonic performance or to provide additional clearance.

The speaker uses a magnetic perforated steel grill.

This speaker is ideally suited for high-rise construction projects of hotels, condominiums and apartments. This speaker is also a great solution when you find an obstruction like ducting or pipes in the location of a speaker.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 7/32" to 1".

Limited lifetime warranty assures you of superior trouble free operation.



BACK



GRILL



SIDE

SPECIFICATIONS

Drivers	(3) 3" Treated Paper Cone with Butyl Rubber Surround
Midrange	(1) 3" Treated Paper Cone with Fabric Surround
Tweeter	20mm Silk Dome
Grill Specifications	Perforated Steel Magnetic Grill with Scrim Cloth
Frequency Response	95Hz-20kHz
Impedance (nominal)	8Ω, Fixed Crossovers
Power Handling	5-50 Watts
SPL	89dB 1W/1m
Diameter x Depth	10 11/16" (272mm) x 1 15/16" (50mm)
Retrofit Cutout Diameter	9 9/16" (242mm)
Mounting Depth	Without Backbox: 1 3/4" (45mm) With Backbox: 2" (51mm)

Part Number [BCS3SDMG](#)

Manual URL www.currentaudio.com



(619) 937-0348
www.CurrentAudio.com

All product specifications are subject to change without notice.
Rev. BCS3SDMG 10/19