



DFS SERIES

Experience the power of deep, immersive sound with the TruAudio DFS powered subwoofer. Featuring a 12" or 10" driver within a sealed enclosure and down-firing design, this subwoofer delivers robust bass that seamlessly integrates into any home theater or music system. Available in both black and white finishes, the TruAudio DFS is designed to complement your space with elegance.

Equipped with a powerful 500-watt internal amplifier, the DFS subwoofer ensures your movies, music, and games are enhanced with rich, resonant bass. Its combination of advanced technology and sleek aesthetics makes the TruAudio DFS Powered Subwoofer a perfect addition to any entertainment setup.



DFS-12

Speaker Type: 12" Powered Subwoofer
 Woofer: 12" polypropylene bonded
 Power: 500 Watts RMS internal amplifier
 Crossover: 40-200 Hz continuously variable low pass
 Frequency Response: 30-200 Hz
 Sensitivity: 200mV @ 250W
 LP Frequency Range: 30-200 Hz (+/- 3dB)
 Enclosure: Downfiring
 Inputs: (2) R/L RCA, (1) LFE
 Controls: Volume, high frequency pass, phase, auto, standby
 Finish: Matte black or white
 Certifications: C-Tick, FCC SDOC, CTUVus, UKCA-LVD, CE-LVD, ERP
 Dimensions: 16.4"x16.4"x16.3"(416x416x414mm)



DFS-10

Speaker Type: 10" Powered Subwoofer
 Woofer: 10" polypropylene bonded
 Power: 300 Watts RMS internal amplifier
 Crossover: 40-200 Hz continuously variable low pass
 Frequency Response: 30-200 Hz
 Sensitivity: 200mV @ 250W
 LP Frequency Range: 33-200 Hz (+/- 3dB)
 Enclosure: Downfiring
 Inputs: (2) R/L RCA, (1) LFE
 Controls: Volume, high frequency pass, phase, auto, standby
 Finish: Matte black or white
 Certifications: C-Tick, FCC SDOC, CTUVus, UKCA-LVD, CE-LVD, ERP
 Dimensions: 14.4"x14.4"x14.1"(368x368x358mm)

