



**A.1-ICSUB8-T50**



## **A.1-ICSUB8-T50**

This pre-built package is designed to easily add an in-ceiling subwoofer to any distributed audio system.



## STREAMING & SPEAKER AMPLIFIER



**VSSL A.1x**

Zones	1
Channels	2
Output Power	35 W @ 8Ω RMS, 50W @ 4Ω RMS
Inputs	(1) Network, (1) Digital Coax, (1) Optical, (1) RCA, (1) IR
Wireless Inputs	Airplay2/Chromecast built-in/Spotify Connect/Bluetooth
WiFi	2.4/5.8 GHz dual antenna MIMO
Outputs	(1) RCA line level, (1) Optical, (1) Digital Coax, (1) Subwoofer
Sub Out	RCA, Adjustable cross over 55-200Hz or by-pass for full range

EQ	7-band adjustable
S/N Ratio	>89dB A-weighted
Freq. Response	20-20kHz
Operating Voltage	115-240 VAC 50/60Hz
Rack Space	1U
Dimension No Feet	7 7/16" W x 8 11/16" D x 1 11/16" H
Dimensions with Feet	7 7/16" W x 8 11/16" D x 2" H
Shipping Weight	3.5 lbs

## SUBWOOFER AMPLIFIER

### T50

Channels:	2 Channels
Power Output, Continuous:	50 Watts / Ch @ 8Ω 60 Watts / Ch @ 4Ω
Bridged Power Output:	100 Watts / Ch @ 8Ω 60 Watts / Ch @ 4Ω
Power Requirements:	120V - 240V @ 50 Hz - 60 Hz A/C
Impedance:	4 - 8 Ω
Inputs:	(1) Stereo RCA, (1) ToS
Outputs:	(1) 3.5mm, (1) Subwoofer (with option of 70Hz crossover or full range)
Control:	(1) 3.5mm IR with built in learning. IR receiver also included
Dimensions:	1.75" (44.5mm) H 6.5" (165mm) W 5.2" (132mm) D
Weight:	2.25 lbs
Certifications:	CE, FCC
Family:	UNIVERSAL



## SUBWOOFER



### IC-SUB-8

Speaker Type	In-Ceiling Subwoofer
Driver	8" Polypropylene
Power	75-150W
Impedance	8Ω
Frequency Response	38-140Hz
Max dB Output	98
Grill Type	Micro perforated
Tweeter	None
Weight	6.7 lbs
Depth	7.9" (201 mm)
Cut Out Diameter	9.4" (238 mm)
Finish Diameter	10.6" (269 mm)

Family UNIVERSAL