



C SERIES | THIN SERIES

When it comes to interior design, aesthetics are just as important as performance—and TruAudio's C and THIN Series in-ceiling speakers strike the perfect balance between the two. Designed to blend seamlessly into your ceiling, these speakers deliver high-end sound without disrupting your décor. Packed with features typically reserved for floor-standing models, the C and THIN Series offers a wide range of options to suit nearly any application.



CP-6

Speaker Type: In-ceiling, 2 way
Woofers: 6.5" polypropylene
Tweeter: 0.75" silk soft dome, swivel
Power: 80 watts
Impedance: 8 Ω
Freq Response: 52 - 20k Hz (+/-3 dB)
Sensitivity: 90 dB
Grill Type: Micromesh, aluminum
Finish Dims: 9.5" (241mm) diameter
 3.1" (79mm) deep
Cutout Dims: 8.3" (211mm) diameter
Family:



THIN-CEILING-P

Speaker Type: In-ceiling, 2-way
Woofers: 5" injected polypropylene
Tweeter: 1" silk soft dome
Power: 5-75 watts
Impedance: 8 Ω
Freq Response: 65 - 20k Hz (+/-3 dB)
Sensitivity: 90 dB
Grill Type: Frameless steel, backbox included
Finish Dims: 6.75" (171mm) diameter
 2.38" (60mm) deep
Cutout Dims: 5.5" (140mm) diameter



Back Box Included

CL-70v-6

Speaker Type: In-Ceiling 70v 2-way
Woofers: 6.5" polypropylene
Tweeter: 0.75" PEI
Power: 60 watts
Impedance: 8 Ω or 70v/100v
70v Taps: 2.5, 5, 10, 15, 25W
100v Taps: 5, 10, 15, 25W
Freq Response: 60 - 20k Hz (+/-3 dB)
Sensitivity: 88 dB
Grill Type: Aluminum mesh
Colors Available: White
Mounting: ---
Finish Dims: 9.5" (241mm) diameter
 5.9" (150mm) deep
Cutout Dims: 8.3" (211mm) diameter
Family:



Now with Ghost Style Grill

Metal Back Box Included

CL-70v-6UL

Speaker Type: In-Ceiling 70v 2-way
Woofers: 6.5" polypropylene
Tweeter: 0.75" PEI
Power: 60 watts
Impedance: 8 Ω or 70v/100v
70v Taps: 2.5, 5, 10, 15, 25W
100v Taps: 5, 10, 15, 25W
Freq Response: 60 - 20k Hz (+/-3 dB)
Sensitivity: 88 dB
Grill Type: Ghost style, frameless
Colors Available: White
Mounting: ---
Finish Dims: 10.4" (264mm) diameter
 9" (229mm) deep

