




## **T50**

This 2-channel class D power amplifier features a mono or stereo speaker output, with support for 4-ohm and 8-ohm speakers. It can deliver 50 watts per channel into 8-ohm loads or 60 watts per channel into 4-ohm loads. Stereo looping outputs allow you to chain amplifiers together to create additional audio zones. Budget-friendly and versatile, it is compatible with dual voltage 110V/220V, can be programmed to work with any TV or control system and you can easily add bass with the sub-out. IR remote and wall-mount brackets are included. Optional AMP-CAN allows amp to easily disappear behind the TV.



### T50

<b>Channels:</b>	2 Channels
<b>Power Output, Continuous:</b>	50 Watts / Ch @ 8Ω 60 Watts / Ch @ 4Ω
<b>Bridged Power Output:</b>	100 Watts / Ch @ 8Ω 60 Watts / Ch @ 4Ω
<b>Power Requirements:</b>	120V - 240V @ 50 Hz - 60 Hz A/C
<b>Impedance:</b>	4 - 8 Ω
<b>Inputs:</b>	(1) Stereo RCA, (1) ToS
<b>Outputs:</b>	(1) 3.5mm, (1) Subwoofer (with option of 70Hz crossover or full range)
<b>Control:</b>	(1) 3.5mm IR with built in learning. IR receiver also included
<b>Dimensions:</b>	1.75" (44.5mm) H 6.5" (165mm) W 5.2" (132mm) D
<b>Weight:</b>	2.25 lbs
<b>Certifications:</b>	CE, FCC
<b>Family:</b>	 UNIVERSAL